

Internal Calibration Equipment Certificates Index

Revision: 03rd January 2020

WEIGHTS & MASSES

| Certificate Number | Calibration Date | Pass Fail | Next Calibration Due | Serial Numbers | Details |
|--------------------|------------------|-----------|----------------------|--|------------------------------------|
| 93916 | 24-12-2019 | Pass | DECEMBER 2021 | 1957 to 1964, 2001 to 2062, 3020 to 3026, 3362A to 3362M, 3500 to 3504 3506 to 3521 & TB4 | SET MC3 112 x Cast Iron |
| 91986_21 | 28-12-2017 | Pass | DECEMBER 2020 | 1 to 25, 2327 & 2328 | SET MS2 26 x Stainless Steel |
| 93915 | 23-12-2019 | Pass | DECEMBER 2021 | 1927,1929, 1931-1933, 1935, 1966-1969, 1970, 1980, 1981, 1926, 1930, 1971- 1972, 1925, 1973- 1974,1937 | SET MC2 21 x Cast Iron |
| 93917 | 23-12-2019 | Pass | DECEMBER 2021 | 3034 | SET MS1 13 x Stainless Steel |
| 93914 | 23-12-2019 | Pass | DECEMBER 2021 | 1910, 1911, 1913-1916, 1921, 1928, 1940, 1975- 1976. | SET MC1 11 x Cast Iron |
| 91706 | 05-09-2017 | Pass | SEPTEMBER 2020 | CL1 to CL5 | SET MB3 5 Brass |
| 92010 | 05-01-2018 | Pass | JANUARY 2023 | S1 01 to S1 28 | SET S1 |
| 93334_21 | 16-05-2019 | Pass | MAY 2024 | S2 01 to S2 27 | SET S2 |
| 93335_21 | 20-05-2019 | Pass | MAY 2024 | S3 01 to S3 27 | SET S3 |
| 92622 | 10-08-2018 | Pass | AUGUST 2023 | S4 01 to S4 14 | SET S4 - A |
| 92623 | 10-08-2018 | Pass | AUGUST 2023 | S4 15 to S4 18 | SET S4 - B |
| 93835 | 27-11-2019 | Pass | NOVEMBER 2023 | S5 01 to S5 27 | SET S5 |

OTHER EQUIPMENT

| Certificate Number | Calibration Date | Pass Fail | Next Calibration Due | Serial Numbers | Details |
|--------------------|------------------|-----------|----------------------|----------------|---|
| 93205 | 29-03-2019 | Pass | MARCH 2020 | 4101220/1053 | TM0260 Hanna Checktemp 1 Temperature Indicator |
| 015517 | 20-09-2019 | Pass | SEPTEMBER 2022 | SGS0584 | TORQUE CALIBRATION BEAM |
| 013555 | 15-06-2018 | Pass | JUNE 2021 | SGS0591 | TORQUE CALIBRATION BEAM |

N.B. Weights, masses and other equipment as listed above placed within the calibration laboratory must temperature acclimatise for at least two hours before use.